



TK-5210G/5310G

VHF/UHF FM & Project 25 Digital Portable Radios



FleetSync®

GENERAL FEATURES

- 5 Watt (136-174 MHz)
- 4 Watt (450-520, 380-470 MHz)
- 100 Zones / 1024 Channels
- Personality Lists
- Backlit Dot Matrix LCD
- 16 Character Alphanumeric Aliases
- 3-Digit Sub-Display
- Function / Status LCD Icons
- RSSI Indicator
- Transmit / Busy / Call Alert / Warn LED
- On/Off Volume Knob
- 16-Position Selector Knob
- 2-Position PF Lever Switch
- 3-Position PF Concentric Switch
- 4 Front Menu-Driven PF Keys
- 3 Side PF Keys
- Orange Emergency / AUX Key
- 12-Key DTMF / PF Keypad¹
- Enhanced Kenwood Audio
- Voice Annunciation
- VOX Ready
- Emergency Features
- Tactical Group
- Battery Level Indicator
- Transceiver Password

- Date & 12/24 Hour Time Clock
- Windows® Programming & Tuning²
- Windows® Firmware Uploading²
- Self-Programming & Tuning
- Cloning
- Easy Option Port
- Voice Guide & Storage (Option)
- Weather-Sealed Accessory Connector
- MIL-STD-810 C/D/E/F
- IP54/55 Water & Dust Protection
- Immersion (IP66/67/68) Option
- Intrinsically Safe Option

SCAN TYPES (FM & P25)

- Single Zone/Multi-Zone Scan
- Scan Lists
- Conventional Scan
- Limited Talk Group Scan³
- Priority Monitor Scan³
- Dual Priority Scan

FM

- QT / DQT
- Operator Selectable Tone
- Two-Tone Decode / Encode
- Special Alert Tone Patterns⁴

- DTMF Encode / Decode / Stun
- Encryption / ANI Board Control
- Companded Audio
- FleetSync®/II PTT ID / Caller ID Display / Emergency⁵
- MDC-1200 PTT ID / Caller ID Display / Emergency⁵

P25 DIGITAL

- P25 Digital Conventional
- P25 Digital Trunking Option
- AMBE+2™ Enhanced VOCODER
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor / Remote Check
- Radio Inhibit
- Encryption Key Delete
- Encryption Key Zeroize (SCM required)
- Encryption Key Retention (SCM required)
- DES Encryption Options
- AES / DES Encryption Options
- KPG-93 KVL Key Loader Interface Cable⁶
- P25 GPS Location
- P25 OTAR Option



Two models available:
 16-Character LCD, 4 Menu-driven PF Keys
 16-Character LCD, 4 Menu-driven PF Keys, 12-Key DTMF/PF Keypad
 (Not actual size)

Options

<ul style="list-style-type: none"> KNB-54N Ni-MH Rechargeable Battery Pack (2500 mAh) KNB-41NC Ni-MH Battery Pack Intrinsically Safe (2500 mAh) KNB-43L Li-Polymer Rechargeable Battery Pack (3300 mAh) KNB-49PL Primary Lithium Non-Rechargeable Battery (4500 mAh) KBP-6 Battery Case 	<ul style="list-style-type: none"> KSC-32 Tri-chemistry Rapid Charger KPG-93 KRA-25 VHF High Gain Antenna KRA-26 VHF Helical Antenna KRA-27 UHF Whip Antenna 	<ul style="list-style-type: none"> KRA-28 VHF Broad Band Antenna (140-170 MHz) KRA-29 UHF Broad Band Antenna (380-430 MHz) KMC-26 Speaker Microphone with Antenna Connector KMC-41M MIL-STD & IP54/55 Speaker Microphone KMC-42WM MIL-STD & IP54/55/66/67 Speaker Microphone 	<ul style="list-style-type: none"> KEP-1 Heavy Duty Earphone KHS-11 2-Wire Palm Mic with Earphone KHS-14 Lightweight Single Muff Headset KBH-11 Belt Clip (2.5") VGS-1 Voice Guide & Storage Unit
---	--	--	---

Specifications

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Model	TK-5210G	TK-5310G
GENERAL		
Models (Type 1)		
4-key w/LCD Model	TK-5210GK2	TK-5310GK2
Full key w/LCD Model	TK-5210GK3	TK-5310GK3
Models (Type 2)		
4-key w/LCD Model		TK-5310GK5
Full key w/LCD Model		TK-5310GK6
Frequency Range		
Type 1	136-174 MHz	450-520 MHz
Type 2		380-470 MHz
Max. Channels per Radio		1024
Zones		100
Max. Channels per Zone		512
Channel Spacing		
Analog	12.5 / 15 / 20 / 25 / 30 kHz	12.5 / 25 KHz
Digital	12.5 kHz	12.5 kHz
Operating Voltage		7.5 VDC ± 20 %
Battery Life 5-5-90 (10-10-80) duty cycle		
KNB-54N, 7.5 VDC, 2500 mAh		12 hours (8 hours)
KNB-41NC, 7.5V DC, 2500mAh		12 hours (8 hours)
KBP-6, AA Alkaline x6 Batteries (@ 1W)		8 hours (5 hours)
Operating Temperature Range	-22° F to +140° F (-30° C to +60° C)	
Frequency Stability (-22° F to +140° F)	± 2.0 ppm	
Antenna Impedance	50 Ω	
Dimensions (W x H x D) (projections not included)		
with KNB-54N	2.28 x 6.10 x 1.80 in. (58 x 155 x 45.7 mm.)	
with KNB-41NC	2.28 x 6.10 x 1.84 in. (58 x 155 x 46.7 mm.)	
with KBP-6	2.36 x 6.10 x 1.84 in. (60 x 155 x 46.7 mm.)	
Weight (Radio only)		
4-key w/LCD Model	11.64 oz. (330 g)	
Full key w/LCD Model	11.64 oz. (330 g)	
Weight with antenna & Belt Clip (4-Key w/LCD model)		
with KNB-32N	23.28 oz. (660 g)	
with KNB-41NC	24.00 oz. (680 g)	

Model	TK-5210G	TK-5310G
GENERAL		
FCC ID	Type 1 Type 2	ALH35733110 ALH39913110
IC Certification	Type 1 Type 2	282D-35733110 282D-39913120
RECEIVER		
Sensitivity		
Digital (5 % BER)		0.25 μV
Digital (1 % BER)		0.40 μV
Analog 12 dB SINAD		0.25 μV
Selectivity		
Digital		-60 dB
Analog @ 25/30 kHz	-78 dB	-75 dB (25 KHz)
Analog @ 12.5 kHz		-67 dB
Intermodulation Distortion		
Digital		-75 dB
Analog @ 25/30 kHz	-75 dB	-75 dB (25 KHz)
Analog @ 12.5 kHz		-68 dB
Spurious & Image		
Digital	-80 dB	-75 dB
Analog	-80 dB	-75 dB
Audio Distortion		
Digital		Less than 1.5 %
Analog		Less than 2 %
Audio Output		500 mW / 8 Ω
TRANSMITTER		
RF Power Output	5 W / 1 W	4 W / 1 W
Spurious & Harmonics		70 dB
FM Hum & Noise		
Analog @ 25 kHz	50 dB	48 dB
Analog @ 12.5 kHz	45 dB	42 dB
Audio Distortion		
Modulation		Less than 2 %
	16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D	

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
Immersion(option)	512.1/Procedure I	512.2/Procedure I	512.3/Procedure I	512.4/Procedure I
International Protection Standard				
Dust & Water Protection	IP54/55			
Dust & Water Jet Intrusion	IP66*			
Immersion	IP67/68*			

Analog measurements made per TIA/EIA 603
Digital measurements made per TIA/EIA 102CAAA

Specifications are subject to change without notice, due to advancements in technology.

FleetSync® is a registered trademark of JVC KENWOOD Corporation in the United States and/or other countries. Windows® is a registered trademark of Microsoft Corporation in the United States and other countries. AMBE+2™ is a trademark of Digital Voice Systems Inc. The P25 Logo is used under license and is a registered trademark of the Project 25 Technology Interest Group.

footnotes from front:

- LCD models only.
- LCD, keypad model only.
- KPG-95DG Software: Windows® 98/NT/2000/Me/XP/Vista (32 bit) compatible.
- P25 Trunking Option required.
- Operates for 2-Tone, DTMF, FleetSync® selective calling in FM mode only.
- Either MDC-1200 or FleetSync® can be activated per radio.
- K7 model is not compatible with AES / DES encryption options.
- KPG-93 adapts the Motorola®, KVL3000/3000 Plus Key Loader to the TK-5210G/5310G.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265
Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.ca


www.kenwoodusa.com



ISO9001 Registered
Communications Equipment Division
Professional Systems Business Group
JVC KENWOOD Corporation

ADS#28212 Printed in USA