

P25 Mission Critical - Federal

VIKING VP600

700/800 MHz • VHF • UHF • SN/SZ • P25 PHASE 1 & 2

With a top display and best in the industry audio performance, the VP600 single band portable offers smarter visual and audio features that make first responder communications effortless. (GSA contract # GS-35F-0675K)



FEATURES

- Mixed protocol operation (Phase 1 & 2, SmartNet®/SmartZone®, FM Analog)
- Mixed protocol zones (each channel in a zone can be from a different system)
- JF-12 certification
- 2048 channels
- Public safety ergonomics with large glove friendly knobs
- Top flip display changes text orientation for viewing while in holster
- Backlight on top display changes for event indication (ex. emergency turns display orange)
- Multiple visual indicators including battery health & signal strength
- 1 Watt audio output for high noise environments
- Voice annunciation & custom announcement creation
- Fully ruggedized - IP67 & MIL-STD-810 C/D/E/F
- Dual Shield design (internal metal housing & an external polycarbonate casing for exceptional durability)
- Available in three keypad options (none, limited, full)
- Integrated GPS (700/800 MHz only)
- MDC-1200 & GE-Star signaling
- P25 Authentication
- Encryption
 - ARC4™ software encryption; compatible w/Motorola ADP™
 - P25/TIA defined: AES-256
 - DES-OFB
 - Over-the-Air-Rekeying (OTAR)
 - VK5000 or Motorola KVL3000/KVL4000 Keyloaders

COMPATIBLE WITH MULTIPLE P25 SYSTEMS

- EJohnson ATLAS® P25 System
- Motorola® Systems
 - Motorola Astro® 25 - P25 Phase 1 & Phase 2
 - Motorola Astro® SmartNet®/SmartZone®
- Harris VIDA® - P25 Phase 1 & Phase 2
- Airbus (formerly Cassidian) VESTA™ Radio - P25 Phase 1 & Phase 2

ACCESSORIES

Complete line of accessories including microphones, speakers & antennas.
 Download the accessory catalog at www.efjohnson.com/products/accessories.

We combine P25 design expertise with recognized quality & reliability along with smarter technology to make KENWOOD Viking radios simple to use & maintain.



Perpetual Software Licensing

Adds greater value to your radios by extending the life of the software into your next hardware platform — you own the software option forever, and your licenses are simple to manage with our cloud-based tool — Vault™.



Armada® Fleet Management

Update radios in a group rather than one at a time. One template programs both portables & mobiles. Supports either direct computer connection or Over-the-Air Programming (OTAP). Elite battery management enables wireless tracking of battery fleet.



TrueVoice™ Noise Cancellation

Software-based noise cancellation automatically filters out noise source frequencies and eliminates the need for extra configuration. Works in analog or digital mode and with any accessory.



Viking VP600 Portable SPECIFICATIONS

GENERAL	700/800	VHF	UHF
Frequency Range	762-806 MHz 806-870 MHz	136-174 MHz	380-470 MHz
Channel Spacing	12.5 kHz, 25 kHz ¹		
Max Freq. Separation	Full Bandsplit		
FCC Type Acceptance Certification	ATH2425770	ATH2425710	ATH2425720
Canada Type Certification	IC:933B-2425770	IC:933B-2425710	IC:933B-2425720
FCC Emissions Designators	16K0F3E, 14K0F3E, 11K0F3E, 8K10F1D, 8K10F1E, 8K10F7E	11K0F3E, 8K10F1D, 8K10F1E, 8K10F7E	11K0F3E, 8K10F1D, 8K10F1E, 8K10F7E
Input Voltage	7.4 V		
Dimensions (w/o antenna) HxWxD	7.5" x 2.62" x 1.75"		
Weight (w/o standard battery)	12.6 oz		
Case	Polycarbonate-black; Mil-spec camouflage options		
Temperature Range	-30°C to +60°C		
Vocoder/Noise Cancellation	AMBE+2 version 1.6 TrueVoice™ noise cancellation and audio enhancement		
Programmable Front Display	Backlit LCD Status Bar (time, date, signal strength, battery level), icon or text display options Up to 4 rows of 12 character lines		
Programmable Top Display	Backlit LCD Status Bar (time, date, signal strength, battery level) or text display options Up to 2 rows of 12 character lines		
TRANSMITTER	700/800	VHF	UHF
RF Power Output	2.5/3 W	5 W	4 W
Frequency Stability (-30°C to +60°C)	1.5 ppm		
Modulation Limiting 25 kHz Channels	5 kHz ¹		
Modulation Limiting 12.5 kHz Channels	2.5 kHz		
Emissions (Conducted/Radiated)	75 dBc		
Audio Response	+1, -3 dB		
FM Hum and Noise 25 kHz Channels	50 dB	56 dB ¹	47 dB
FM Hum and Noise 12.5 kHz Channels	44 dB	50 dB	47 dB
Audio Distortion	1%		
RECEIVER	700/800	VHF	UHF
Audio Power Output	1 W rated 2.5 W Max		
Frequency Stability (-30°C to +60°C)	1.5 ppm		
Analog Mode Sensitivity: 12 dB SINAD	-120 dBm	-122 dBm	-119 dBm
Digital Mode Sensitivity: 5% BER	-120 dBm	-122 dBm	-119 dBm
Selectivity: 25 kHz Channels	75 dB ¹		
Selectivity: 12.5 kHz Channels	60 dB		
Intermodulation	75 dB		
Spurious & Image Rejection	80 dB		
FM Hum and Noise 25 kHz Channels	50 dB ¹		
FM Hum and Noise 12.5 kHz Channels	44 dB		
Audio Distortion	1.5%		

Note 1: 25 kHz mode is not available in US FCC frequencies in 700 MHz, UHF or VHF.


BATTERY	Dimensions (HxWxD)	Weight	Capacity
High Capacity Lithium Ion	6.5" x 2.3" x .78"	8.1 oz	3780 mAh

Specifications are measured per TIA 102.CAAA-C, TIA 102.CAAB-C and per TIA 603-D.

All specifications are subject to change without notice. Please check the website for the latest version.
V.04.06.17 © Copyright 2017 EF Johnson Technologies, Inc. (E.F. Johnson Company is operating entity)
AMBE+2™ is a trademark of Digital Voice Systems Inc.

Environmental Specifications 		
Environment	Mil Spec	810G
	M	P
Low Pressure	500.5	II
High Temp.	501.5	II
Low Temp.	502.5	II
Temp. Shock	503.5	I-D
Solar Radiation	505.5	I
Rain/Blown Rain	506.5	I
Humidity	507.5	I
Salt Fog	509.5	NA
Dust and Sand	510.5	I
Vibration	514.6	I
Shock	516.6	VI, V
Immersion	512.5	I

M=Method, P=Procedure
Also meets equivalent superseded C, D, E, and F standards.
Immersion meets IEC 529 IP67

Encryption Options 	
Supported Encryption	AES, DES-OFB, ARC4
Encryption Key/Radio	126 Common Key Reference (CKR), 126 Physical Identifier, (PID), Compatible w/ Motorola Key Variable Loader
Encryption Frame Re-sync Interval	P25 CAI 360 MSEC
Encryption Keying	External Key Loader, OTAR
Mode	OFB-Output Feedback
Encryption Type	Digital
Key Erasure	Keyboard Command
Standards	FIPS 46-3, FIPS 81, FIPS 140-2, FIPS 197

HAZARDOUS LOCATION CERTIFICATION	
Certification Lab	FM Approvals (FM)
Standard Applied	FM3611
Classification Rating	Class I, Division 2, Groups A, B, C, D
Approved Battery	5875700373 (identified by lack of release button & presence of key slot on bottom of battery)
Approved Speaker Microphones	5893211B18, 5893211B24, 5893211B30, 5893211G18, 5893211G24, 5893211G30 (KENWOOD Viking Premium Speaker Mic w/ options for black or high visibility & three cord lengths)

EF Johnson Technologies, Inc.
1440 Corporate Drive, Irving, TX 75038-2401
Phone: 800.328.3911 • efjohnson.com

a JVCKENWOOD Company